


ANALOGIC SOLENOID CONSTANT DOSING PUMP

DESCRIPTION

- Analogic solenoid constant dosing pump
- Easy to Install and minimum maintainance required
- Frequency adjustable from 0 to 120 pulses per minutes by potentiometer
- ON / OFF function
- Reinforced PP body
- Polycarbonate front panel
- Pump head with Manual bleed
- IP 54 Protection Degree
- Standard Power Supply 230 Vac
- 100% Made in Italy
- CE approved

OPTIONAL

- SCHUKO plug
- ON/OFF switch
- PVDF pump head with PTFE seals (suitable to dose High Concentration Sodium Hypochlorite or strong Oxidizing agents)




TECHNICAL SPECIFICATIONS											
Standard	Max l/h	Pressure		Max cc / imp	Stroke	Solenoid	Pump Head	Power [Watt]	Pulses	Weight	
		Bar	PSI							kg.	Lbs
LIP VALVE VERSION											
05-02	05	02	29,4	0,69	1,3	Ø 80	PP	50	120	3	5,7
04-05	04	05	73,5	0,55	1,3	Ø 80	PP	50	120	3	5,7
03-07	03	07	103	0,41	1,3	Ø 80	PP	50	120	3	5,7
BALL VALVE VERSION											
1,5-11	1,5	11	162	0,21	1,1	Ø 80	PP	50	120	3	5,7
03-09	03	09	132	0,41	1,3	Ø 80	PP	50	120	3	5,7
05-05	05	05	73,5	0,69	1,3	Ø 80	PP	50	120	3	5,7
07-02	07	02	29,4	0,97	1,3	Ø 80	PP	50	120	3	5,7

ME2-CA

ANALOGIC SOLENOID CONSTANT DOSING PUMP

DIMENSIONI E INGOMBRI (MM)



STANDARD KIT					
	Injection Valve	PP Foot filter with lip valve	Delivery tube 2mt PE 4x6	2mt PVC 4x6 Suction tube	1,5mt PVC 4x6 Bleed tube
STANDARD KIT	