

MP3

PERISTALTIC PUMP WITH FIXED FLOW RATE

DESCRIPTION

- Peristaltic pump with fixed flow rate
- Reinforced PP body
- Front cover glass built in SAN
- Standard Power Supply 230 Vac
- 100 % Made in Italy
- CE approved
- Small size
- Easy to install and minimum maintenance required
- Safe and reliable
- PBT roller holder
- DELRIN roller



TECHNICAL SPECIFICATIONS

Standard	Max l/h	Pressure		Max cc / min	Tube	Hose Dimensions	Box	Power [Watt]	RPM	Weight	
		Bar	PSI							kg.	Lbs
230 Vac VERSION											
1,5 - 01	1,5	1	14,5	25	Santoprene	5,8 x 9,3	PP	35	10	0,35	0,8
03 - 01	03	1	14,5	50	Santoprene	5,8 x 9,3	PP	35	20	0,35	0,8
04 - 01	04	1	14,5	66,67	Santoprene	6,4 x 9,6	PP	35	30	0,35	0,8
0,5 - 03	0,5	3	43,5	8,33	Silicon	5 x 10	PP	35	5	0,35	0,8
01 - 03	01	3	43,5	16,67	Silicon	5 x 10	PP	35	10	0,35	0,8
24 Vdc VERSION											
04 - 01	04	1	14,5	66,67	Santoprene	5,8 x 9,3	PP	35	32	0,35	0,8
06 - 01	06	1	14,5	100	Santoprene	5,8 x 9,3	PP	35	42	0,35	0,8
12-01	12	1	14,5	200	Santoprene	5,8 x 9,3	PP	35	102	0,35	0,8
16-01	16	1	14,5	266,67	Santoprene	5,8 x 9,3	PP	35	150	0,35	0,8
20-01	20	1	14,5	333,33	Santoprene	5,8 x 9,3	PP	35	160	0,35	0,8

MP3

PERISTALTIC PUMP WITH FIXED FLOW RATE

PUMP VIEW (MM)

